



The Locking Dome Strainer Kit meets or exceeds UPC 810.4-Strainers, and IPC 802.3-Waste Receptors as referenced below:

Waste receptors shall be of an approved type. A removable strainer or basket shall cover the waste outlet of waste receptors.

Description:

The Locking Dome Strainer Kits are designed to prevent debris from entering the drain openings of indirect waste receptors. They are designed for use in new construction and retro-fit applications for drains in existing buildings.

Construction:

1 - #14 x 6" type 316 stainless steel screw for superior corrosion resistance.

1 - 5 1/2" W x 3" H Dome Strainer made from engineered polymers to provide impact resistance, chemical resistance and heat resistance up to 215 degrees Fahrenheit.

1 - Cross Strainer made from engineered polymers to provide impact resistance, chemical resistance and heat resistance up to 215 degrees Fahrenheit.

2 - Gaskets made from polyethylene to ensure a proper fit in various applications.

NOMINAL PIPE SIZE	MODEL#	"A"	"B"	"C" -(PVC GASKET)	"C" -(CAST IRON GASKET)
2"	LDomeSK2	6"	5 1/2"	1.95"-2.00"	2.00"-2.05"
3"	LDomeSK3	6"	5 1/2"	2.95"-3.00"	3.00"-3.05"
4"	LDomeSK4	6"	5 1/2"	3.95"-4.00"	4.00"-4.05"